

DOOSAN

DL350-5 WHEEL LOADER

NEW MODEL OVERVIEW



- T4 Emission Compliant (HPCR, CEGR, DOC & SCR)
- Standard Z-Bar (High Lift Z-Bar Available)
- Limited Slip Differentials
- Selectable Work Modes (Eco, Normal & Power)
- Separate Cooling and Engine Compartments, Variable Speed Reversing Cooling Fan, Exhaust Heat Exchanger
- Telematics — 3 Year Subscription
- Options — Hydraulic Locking Front & Conventional Rear Differential, Emergency Steer, 5 Gear with Lock-up Clutch, Hydraulic Load Isolation System, Finger Tip Three Lever Controls, Electric Joystick Steering, Rotating Beacon, Rear View Camera, 110 Volt Plug Heater, Auto Greasing System, Rubber Fender Protectors, Full Fender with Rubber Protector

| NEW MODEL OVERVIEW | DL350-5 |
|--|---|
| Rated Power – Gross (HP per SAE J1995) | 271 hp (202 kW) @ 1800 rpm |
| Operating Weight | 43,530 lb. (19 745 kg) |
| Static Tipping Load (Straight) | 34,657 lb. (15 720 kg) |
| Static Tipping Load (Full Turn) | 30,600 lb. (13 880 kg) |
| Maximum Dumping Height | 10' (3040 mm) |
| Bucket Capacity Heaped | 4.6 yd ³ (3.5 m ³) |
| Bucket Hinge Pin Height | 13' 8" (4170 mm) |
| Breakout Force | 36,869 lbf. (16 723 kgf) |
| Maximum Dump (Reach @ full height) | 4' (1220 mm) |
| External Radius, Bucket Edge | 21' 8" (6615 mm) |

PL-1007-0414

DOOSAN DELIVERS

equipment for tough jobs

*Specifications and design are subject to change without notice. Pictures of Doosan products may show other than standard equipment. All dimensions are shown in inches. For more information refer to Doosan Dealer Net. Pictured machine is a DL350-3.