

DOOSAN

DL420-5 WHEEL LOADER

NEW MODEL OVERVIEW



- T4 Emission Compliant (HPCR, CEGR, DOC & SCR)
- Standard Z-Bar (High Lift Z-Bar Available)
- Limited Slip Differentials
- Selectabel Work Modes (Eco, Normal & Power)
- Separate Cooling and Engine Compartments, Variable Speed Reversing Cooling Fan, Exhaust Heat Exchanger
- Telematics — 3 Year Subscription
- Options — Hydraulic Locking Front & Conventional Rear Deifferential, Axle Oil Cooler, Emergency Steer, 5 Gear with Lock-up Clutch, Hydraulic Load Isolation System, Finger Tip Three Lever Controls, Electric Joystick Steering, Rotating Beacon, Rear View Camera, 110 Volt Plug Heater, Auto Greasing System, Rubber Fender Protectors, Full Fender with Rubber Protector

NEW MODEL OVERVIEW	DL420-5
Rated Power – Gross (HP per SAE J1995)	345 hp (257 kW) @ 1,800 rpm
Operating Weight	50,784 lb. (23 035 kg)
Static Tipping Load (Straight)	40,257 lb. (18 260 kg)
Static Tipping Load (Full Turn)	35,550 lb. (16 125 kg)
Maximum Dumping Height	10' 1" (3075 mm)
Bucket Capacity Heaped	5.5 yd ³ (4.2 m ³)
Bucket Hinge Pin Height	14' 1" (4280 mm)
Breakout Force	47,210 lbf. (21 414 kgf)
Maximum Dump (Reach @ full height)	4' 1" (1240 mm)
External Radius, Bucket Edge	22' 10" (6955 mm)

PL-1008-0514

DOOSAN DELIVERS

equipment for tough jobs

*Specifications and design are subject to change without notice. Pictures of Doosan products may show other than standard equipment. All dimensions are shown in inches. For more information refer to Doosan Dealer Net.