

DOOSAN

DL250-5

WHEEL LOADER

NEW MODEL OVERVIEW



- T4 Emission Compliant (HPCR, CEGR, DOC & SCR)
- Standard Z-Bar (High Lift Z-Bar available)
- Limited Slip Differentials
- Selectable Work Modes (Eco, Normal & Power)
- Separate Cooling and Engine Compartments
- Variable Speed Reversing Cooling Fan
- Exhaust Heat Exchanger
- Telematics — 3 Year Subscription
- Options — Hydraulic Locking Front & Conventional Rear Differential, Emergency Steer, Hydraulic Load Isolation System, Fingertip Three Lever Controls, Rotating Beacon, Rear View Camera, 110 Volt Plug Heater, Full Fender with Rubber Protector

NEW MODEL OVERVIEW	DL250-5
Rated Power – Gross (HP per SAE J1995)	172 hp (128 kW) @ 2100 rpm
Operating Weight	30,115 lb. (13,660 kg)
Static Tipping Load (Straight)	23,997 lb. (10,885 kg)
Static Tipping Load (Full Turn)	21,186 lb. (9,610 kg)
Maximum Dumping Height	9' 2" (2800 mm)
Bucket Capacity Heaped	3.27 yd ³ (2.5 m ³)
Bucket Hinge Pin Height	12' 8" (3,860 mm)
Breakout Force	23,830 lbf. (10,810 kgf)
Maximum Dump Reach at Full Height	42" (1,075 mm)
External Radius, Bucket Edge	19' 10" (6,045 mm)

PL-1019-0315

DOOSAN DELIVERS

equipment for tough jobs

*Specifications and design are subject to change without notice. Pictures of Doosan products may show other than standard equipment. All dimensions are shown in inches. For more information refer to Doosan Dealer Net. Pictured machine is a DL250-5.