

TERRAMAC® RT14 RUBBER TRACK CARRIER

Standard RT14 Specs

The Terramac® RT14 features a 28,000 lb. carrying capacity and is sure to get noticed for its ability to tackle the heavy loads. Customizable attachments available, contact your local Dealer or Terramac® factory for more details.

| DIMENSIONS | |
|---|-------------|
| Full Length | 20' 6" |
| Full Height | 10' 5" |
| Width Over Tracks | 9' 8" |
| Min Ground Clearance | 24" |
| Front Overhang | 3' 1.5" |
| Track Gauge (Center-to-Center) | 7' |
| Track Width | 31.5" |
| Undercarriage Length (Idler to Drive Hub) | 12' 4" |
| Dump Bed Loading Height Over Side | 6' 7" |
| Height of Rock Bed Side (Vessel) | 20" |
| Length of Rock Bed (Vessel) | 11' 6" |
| Width of Rock Bed (Vessel) | 9' |
| Dumping Angle | 60° |
| Machine Weight (no bed) | 28,726 lbs. |
| Machine Weight (with rock bed) | 34,260 lbs. |

| ENGINE | |
|-------------------|---------------------------|
| Manufacturer | Cummins |
| Model | QSB 6.7 T4F |
| Displacement | 408 cu. in. |
| Horsepower | 310 HP @ 2200 RPM |
| Electrical System | 12 VDC |
| Battery | (2) GRP 31, 1125 CCA each |
| Fuel Capacity | 82 gallons |



| HYDRAULICS | |
|----------------------------|-------------------|
| Transmission | HST |
| Drive Pump Max Flow (x2) | 64 gpm / side |
| Drive Pump Max Pressure | 5,500 PSI |
| Tandem Gear Pump Max Flow | |
| Front Section (Aux Output) | 30 gpm @ 3000 PSI |
| Rear Section (HST Drive) | 25 gpm @ 500 PSI |

| PERFORMANCE | |
|----------------------------|-------------|
| Max. Carrying Capacity | 28,000 lbs. |
| Travel Speed - 1st Gear | 4.0 mph |
| Travel Speed - 2nd Gear | 6.8 mph |
| Gradability | 58% (30°) |
| Turning Radius | Zero Turn |
| Ground Pressure (loaded) | 7.4 PSI |
| Ground Pressure (unloaded) | 4.9 PSI |

T18141

TERRAMAC[®] RT14 RUBBER TRACK CARRIER

Standard RT14 Units & Dimensions

