



# TERRAMAC® RT9 PERSONNEL CARRIER



## Chauffeur Your Crew with Ease

Transporting people on a job site can be a challenge but the Terramac® Personnel Carrier makes it a cinch! With a maximum capacity greater than any other carrier in its class you will save time and money.

The Terramac® RT9 is an all terrain utility vehicle that is easily maneuvered over rough, soft and steep ground conditions. With a carrying capacity of 18,000 pounds you will have more than enough power to move your crew.

### Features

- 25 person capacity with seat-belts
- ROPS & FOPS certified
- 4 tool boxes accessible from outside
- Fold-down stairs with handrails
- Fully enclosed options available with heat



# TERRAMAC® RT9 PERSONNEL CARRIER

## Standard RT9 Specs\*

### PERFORMANCE

Max. Carrying Capacity	18,000 lbs.
Travel Speed - 1st Gear	2.5 mph
Travel Speed - 2nd Gear	5.4 mph
Gradeability	58% (32°)
Turning Radius	Zero Turn
Ground Pressure (loaded)	6.4 PSI
Ground Pressure (unloaded)	3.8 PSI

### HYDRAULICS

Transmission	HST
Drive Pump Max Flow (x2)	43 gpm / side
Drive Pump Max Pressure	5,500 PSI
Tandem Gear Pump Max Flow	
Front Section (AUX Output)	25 gpm @ 3000 PSI
Rear Section (HST Drive)	22 gpm @ 550 PSI
Optional Pump Drive	25 gpm @ 2500 PSI

### ENGINE

Manufacturer	Cummins
Model	QSB 6.7 T4F
Displacement	408 cu. in.
Horsepower	225 HP @ 2200 RPM
Electrical System	12 VDC
Battery	(2) GRP 31, 1125 CCA ea.
Fuel Capacity	64 gallons

### DIMENSIONS

Full Length	19' 6"
Full Height	9' 11"
Width Over Tracks	8' 3"
Min Ground Clearance	21"
Front Overhang	2' 6"
Track Gauge (Center-to-Center)	6'
Track Width	27.5"
Undercarriage Length	
(Idle to Drive Hub)	12' 3"
Machine Weight (no bed)	21,500 lbs.
Machine Weight (with bed)	26,000 lbs.

\* Based on standard machine. Specifications will vary based on optional equipment selected.

## Personnel Carrier Specs

### DIMENSIONS

178" L x 102" W x 83" H

### WEIGHT

7,000 LBS.

### SEAT LAYOUT

